


Code: LDEURO1BC-BK

Linea-Duo CFX | LINEA-DUO CFX RANGE | EuroFix Apertured Plates complete with Fixing Grid

Product Image




Wiring



Dimensions

Hamilton®
LINEA DUO CFX

EURO1
Single plate with 1 x EuroFix cutout



Insert Type	1 gang EuroFix 25x50mm Apertured Plate with Grid
Insert Colour	No Insert Colour
EAN13 Barcode	5017504039257
Commodity Code	74192000
Luckins TSI	393789070
Dimensions(Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Switched Poles	N/A
Current Rating	Insert Specific
Voltage	Insert Specific
Maximum Load	Insert Specific
IP Rating	N/A
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm ²
Earth Terminal Capacity 2	4x1.5mm ²
Earth Terminal Capacity 3	3x2.5mm ²
Earth Terminal Capacity 4	1x4mm ² Multi-strand
Earth Terminal Capacity 5	1x6mm ²
Product Class 1	Face plate must be earthed
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	N/A

Additional Notes See EuroFix for a full range of inserts. Plates must be Earthed via the Earth Tag.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 5/22/2023 2:03:22 PM E&OE